



DRAGONFLY
a e r o s p a c e



+27 21 206 6556



info@dragonflyaerospace.com



RW-1Nms

High-fidelity reaction wheel for enhanced imaging
satellite stability and performance



ITAR-Free



TRL 9



Specifications

Angular Momentum

Torque

Control Modes

Control Rate (Speed, Torque)

Speed Range

Control Accuracy – Imaging Mode

- Speed Control
- Torque Control

Interface

Supply Voltage

Power @ 0.1 Nms

Peak Power

Operating Temperature

Dimensions

Mass

Unbalance

- Static
- Coupled

Vibration

Radiation

Reliability

Features

1.0 Nms @28.5 V

± 39 mNm (± 74 mNm)*

Current, Speed and Torque

10 Hz

$\pm 10\,000$ RPM

Steady-state speed error < 0.5 RPM

Steady-state momentum error $< 5.09 \times 10^{-5}$ Nms

CAN / RS485

12–36 V

~ 1.2 W

108 W

$-20\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$

102.8 x 100 x 50 mm*

1.0 kg

< 2 g.mm² (< 0.5 g.mm²)*

< 50 g.mm² (< 15 g.mm²)*

14.14 g RMS (GEVS)

> 20 kRad at component level

ABEC 7 bearings for long service life

Over temperature and current protection

Latch-up protection

Regenerative braking

Control timing knowledge < 1 ms

ABOUT DRAGONFLY AEROSPACE

* Version 2

Dragonfly Aerospace is an industry leader in world-class, high-performance imaging satellites and payloads. Our turnkey solutions for imaging satellites get these strategic assets operational on orbit within minimum time, cost and risk.

All features, functionality and other product specifications are subject to change without notice or obligation.

©2024 Dragonfly Aerospace (Pty) Ltd. All rights reserved. THIS DOCUMENT AND THE INFORMATION IT CONTAINS ARE PROPRIETARY TO DRAGONFLY AEROSPACE (PTY) LTD.

DRAGONFLY AEROSPACE (PTY) LTD makes no representations and gives no permission or license to use any part of the information, no warranties of whatever nature in respect of the document, including but not limited to the accuracy or completeness of any information, facts and/or opinions contained therein.